Studsvik

Key Features

PWR and SMR transients.



Next-Generation Nodal Code for LWR Transient Analysis

SIMULATE5-K is an advanced, multi-group nodal code for LWR transient analysis. SIMULATE5-K delivers neutronic and thermal-hydraulic analysis with licensinggrade accuracy over a wide range of transient applications. SIMULATE5-K offers complete consistency with SIMULATE5 methods and results.

SIMULATE5-K (S5K) is an extension of the SIMULATE5 code, which

is capable of modeling (PWR , BWR, and SMR) light water reactor geometry. S5K merges and extends the SIMULATE- 3K functionality into

the SIMULATE5 code. S5K is a best estimate nodal reactor analysis tool

that employs advanced core neutronics coupled with detailed thermal-

hydraulic channel models. Faithful modeling of assembly-by-assembly

neutronic and thermal-hydraulic effects, including assembly pin power

reconstruction, permits the application of S5K to a wide class of BWR,

S5K can be used to analyze a variety of core transients, for example,

BWR stability analysis, reactivity insertion analysis, dynamic rod worth

calculations, and anticipated operational events.

Methodology

S5K leverages the power of SIMULATE5, the industry standard in nodal reactor analysis. By including cutting-edge neutronic methods and advanced engineering features, S5K delivers unparalleled fidelity with production-level run times. S5K solves the transient three-dimensional, multigroup neutron diffusion equations, including an N-group model for delayed neutron precursors. Intranodal flux and power distributions within each node are used to compute the power, fuel temperatures, and enthalpies for every axial level of every fuel pin in the core during transients.

S5K is built on the solid foundation of SIMULATE5, the industry-leading steadystate nodal reactor analysis code.

Core Neutronics

- Multigroup kinetics
- Extended cross section model
- Axial re-homogenization
- Macro/Micro cross section model

Core Channel TH

- · Treatment of all the flow paths in the assembly
- Treatment of non-uniform water rod designs
- Evaluation of steam/water properties at local pressure conditions

Fuel Pin Model

- Supports Accident Tolerant Fuel (ATF)
- Supports double cooled annular fuel

Address Emerging Issues

S5K helps operating utilities address emerging regulatory issues like pin enthalpy and delta-CPR limits. An explicit fuel pin conduction model tracks the complete radial distribution of fuel temperatures and enthalpies in every fuel pin in the core throughout a transient. S5K is capable of evaluating margin-to-thermal limits (such as delta CPR) during plant transients, providing licensing-grade support to core designers.

In addition, S5K supports NRC RG 1.236, given appropriate input data.

PWR Applications

S5K provides licensing-grade support for analyzing PWR specific safety analyses, such as Reactivity Insertion Accidents (RIA) like ejected rods and inadvertent bank withdrawals, dropped rods, and boron dilution accidents.

BWR Applications

S5K provides licensing-grade support for analyzing BWR specific safety analyses and fast operational occurrences where the primary acceptance criteria are fuel rod integrity. BWR analyses include reactor stability and reactivity insertion accidents (RIA) like dropped rods and inadvertent bank withdrawals.

Other Applications

In addition, Studsvik offers a separate SIMULATE5-K-VVER product for VVER plant designs.

Applications

With a robust neutronics engine and advanced thermal-hydraulic capabilities, S5K is wellsuited for transients with a strong neutronic/ thermal-hydraulic coupling in PWRs, BWRs and SMRs. Its seamless



linkage with SIMULATE5 makes S5K the perfect tool for the study of operational transients typically analyzed on a cycle-specific basis. Core designers simply generate the proposed core and seamlessly use S5K to evaluate the prescribed set of transients as part of the core reload design licensing process. For modeling whole-plant transients, S5K can be coupled with system codes like RELAP and TRACE.

The powerful neutronics engine inside S5K guarantees a high-fidelity, 3D core neutronic solution in whole-plant transient simulations.

Features

- Satisfies the NRC RG1.236 requirements by implementing new models for fission gas release, rod pressurization, oxide thickness and hydrogen uptake.
- S5K features multi-group capability
- S5K provides a consistent extension of SIMULATE5 steady-state methods to transients.

Requirements

S5K is available for all standard computing platforms running most modern 64-bit operating systems. Linux and Windows architectures are supported environments for S5K.

Unparalleled Customer Support

Studsvik's technical support is built on putting the needs of its customers first.

- 24-hour response time
- Easy ticketing system
- On-line support portals
- Access to technical documentation
- Active and growing user communities of practice

For further information please contact:

Your Studsvik representative or e-mail: **cms-info@studsvik.com**

www.studsvik.com